

## OPT-618P Series PoE Fiber Switch

100Base-Fx to 6\*10/100Base-Tx(PSE)

RoHS Compliant



### >>Description

OPT-618P series provide 1 fiber port and 6 10/100Base-TX PoE ports, OPT-618P series compliant with IEEE802.3af and IEEE802.3at while transmitting data over the cable. Each port support 30 watts output to PoE terminals directly to provide AC power without additional wiring.

#### Application

- VoIP transmission, Intelligent Home Systems
- Urban Intelligent Traffic Monitoring System (ITS), Safe City, Wireless City
- Highway monitoring system, Electronic road monitoring, Capture system
- Large industrial enterprise security monitoring systems, network multifunction system
- Remote multimedia teaching / Campus monitoring, Video conferencing systems
- Building intercom, Wireless communications, Video surveillance

### >>Main Features

- Complies with IEEE802.3, IEEE802.3u standard
- Supports 802.3x flow control
- Supports IEEE802.3at, IEEE802.3af PoE standard
- Support PD detection and PD classification
- Provides 6-port 10/100M RJ45 and 1-port fiber ports
- Optional VLAN function
- Supports auto duplex(HDX/FDX) auto MDI/MDIX function
- Auto MDI/MDI-X support on RJ-45 port
- Support max forwarding packet length 1552/1536 bytes
- Status LED for easy monitoring of device status
- Fanless design, Natural cooling

## >> Specifications

### Interface

- 6 x Ethernet+PoE port (RJ45) 10/100Base-Tx
- 1 x Optical port (1x9) 100Base-Fx

### Optical Port

- Available for 1310/1490/1550nm Single mode, 1310nm Multi mode
- Transfer Distance: up to 120km
- Connectors: SC, ST and FC optional
- Fiber core: 9/125µm on single-mode fiber; 50/125µm and 62.5/125µm on multi-mode fiber

### Ethernet Port

- Cable: Cat 5/5e/6 UTP cable
- Available speed: force 10Mbps, force 100Mbps and auto-detective 10/100Mbps. Full-Duplex and Half-Duplex auto-negotiation
- Connectors: RJ-45 Connector; MDI/MDI-X connection auto-sensing

### Standard

- IEEE802.3 (10Base-T)
- IEEE802.3u (100Base-TX/FX)
- IEEE802.3x (Flow control)
- IEEE802.3af (Power over Ethernet Standard)
- IEEE802.3at (Power over Ethernet enhancements Standard)

### PoE Specification

- Power Output: PoE 48V DC
- PoE Power Supply type: End-Span
- Power Pin Assignment: 1/2(+), 3/6(-)
- PoE Power Budget: Each port provides max 30W feed power

### LED Indicators

- Power Status, Speed, FX Link/Act, TX Link/Act

### Power Requirement

- 48V DC, External AC to DC adapter

### Physical Characteristics

- Housing: Metal enclosure
- Dimensions: 214 x 105 x 32mm
- Weight: 0.56kg

### Environmental Limits

- Operating Temperature: -10°C to 70°C
- Storage Temperature: -20°C to 70°C
- Operating Humidity: 10% to 90% RH (non-condensing)
- Storage Humidity: 5% to 90% RH (non-condensing)

### Agency Approvals


- FCC Part 15 of Class A & CE approved

### Warranty

- 3 years

## >> Applications

The following illustrates typical applications for the OPT-618P series. The actual distances will depend on several factors including the quality of cables used and the terminal equipment employed.





## >>Ordering Information

---

### **Double Fiber**

OPT-618PM02	100Base-Fx to 6*10/100Base-Tx(PSE), Multi mode, 2Km, SC/ST/FC optional
OPT-618PS25	100Base-Fx to 6*10/100Base-Tx(PSE), Single mode, 25Km, SC/ST/FC optional
OPT-618PS40	100Base-Fx to 6*10/100Base-Tx(PSE), Single mode, 40Km, SC/ST/FC optional
OPT-618PS60	100Base-Fx to 6*10/100Base-Tx(PSE), Single mode, 60Km, SC/ST/FC optional
OPT-618PS80	100Base-Fx to 6*10/100Base-Tx(PSE), Single mode, 80Km, SC/ST/FC optional

### **Single Fiber**

OPT-618PW25	100Base-Fx to 6*10/100Base-Tx(PSE), Bi-Directional, 25Km, SC/ST/FC optional
OPT-618PW40	100Base-Fx to 6*10/100Base-Tx(PSE), Bi-Directional, 40Km, SC/ST/FC optional
OPT-618PW60	100Base-Fx to 6*10/100Base-Tx(PSE), Bi-Directional, 60Km, SC/ST/FC optional
OPT-618PW80	100Base-Fx to 6*10/100Base-Tx(PSE), Bi-Directional, 80Km, SC/ST/FC optional

## >>Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTONE before they become applicable to any particular order or contract. In accordance with the OPTONE policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTONE or others. Further details are available from any OPTONE sales representative.

[sales@optone.net](mailto:sales@optone.net)  
<http://www.optone.net>